



ZIEGLER
Cultivation



GÜLLETECHNIK
LM-TECH

ÜBER ZIEGLER

MISSION & VISION Wir bauen Maschinen, die höchst effizient und robust sind, den Einsatz im Alltag leichter machen und neue Maßstäbe in der Erntetechnik und der Bodenbearbeitung setzen - und das auf internationalem Top-Niveau. Als Mittelstandsunternehmen mit 100-jähriger Tradition entwickeln wir unser Produktportfolio immer weiter und verbessern bestehende Maschinenbaureihen konstant. Denn Landwirte und Lohnunternehmer auf der ganzen Welt erwarten heute guten Service, Qualität und somit viel mehr als Standardprodukte die einfach nur funktionieren. Diese Ansprüche erfüllt ZIEGLER CULTIVATION.

SHORTFACTS

- Hauptsitz und Verwaltung in Pöttmes, Deutschland
- Eigene Produktionsstätten in Nýrany (CZ) und Daugavpils (LV)
- Eigener Vertriebsstandort in Dänemark (Vissenbjerg)
- Firmengelände aller Grundstücke insgesamt ca. 300.000 m²
- Ca. 800 Mitarbeiter gesamt, ca. 250 Vertriebspartner weltweit

ABOUT ZIEGLER

MISSION & VISION We are building machines that are extremely efficient and robust, make everyday use easier and set new standards in harvesting technology and tillage - at the top international level. As a company with a 100-year tradition, we are constantly developing our product portfolio and constantly improving existing machine series. Because farmers and contractors all over the world today expect good service, quality and therefore much more than standard products that just work. ZIEGLER CULTIVATION fulfills these requirements.

SHORTFACTS

- Head office and administration in Pöttmes, Germany
- Own production facilities in Nýrany (CZ) and Daugavpils (LV)
- Own sales office in Denmark (Vissenbjerg)
- Company premises in total are approx. 300,000 m²
- About 800 employees and 250 sales partners worldwide

KONTAKT / CONTACT

Ziegler GmbH
Schrobenhausener Str. 56
86554 Pöttmes (Germany)
Tel: +49 (0) 8253 / 9997-0
Fax: +49 (0) 8253 / 9997-47
vertrieb@ziegler-cultivation.com
www.ziegler-cultivation.com

LM-TECH

www.ziegler-cultivation.com

DISC MASTER LM

Gülfescheibenegge / Slurry disc harrow



EINSATZZWECK

Bei der DISC MASTER LM sind die Gülleausgänge direkt hinter der ersten Scheibenreihe angebracht. Dies hat den Vorteil, dass die Gülle sofort in die bereits gelockerte Erde eingearbeitet und sofort bedeckt wird. Der Güllenschlauch und die Auslässe sind so miteinander verbunden, dass es zu keinen Verstopfungen im Schlauch kommen kann und einen freien Durchlauf garantiert. Die DISC MASTER LM ist mit dem Vogelsang Verteilerkopf ExaCut mit Luftnachsaugung ausgerüstet. Alle Gülle berührenden Teile sind aus rostfreiem Edelstahl gefertigt, alle Lager sind güllerresistent (Hersteller: SKF). Natürlich mit vielen Optionen der normalen Scheibeneggen lieferbar. Weitere Highlights: Kürzere Bauweise gegenüber normalen Scheibeneggen, enorme Flächenleistung, fahrbar mit bis zu 19 km/h und erweiterte Koppelpunkte - somit für nahezu alle Fasshersteller und Selbstfahrer passend.

PURPOSE

On the DISC MASTER LM the liquid manure outlets are located directly behind the first row of discs. This has the advantage that the liquid manure is immediately worked into the already loosened soil and immediately covered. The slurry hose and the outlets are connected in such a way that there can be no blockages in the hose and free flow is guaranteed. The DISC MASTER LM is equipped with the Vogelsang ExaCut distributor head with air suction. All parts that come into contact with manure are made of stainless steel, all bearings are manure-resistant (manufacturer: SKF). Of course it can be supplied with many options for the normal disc harrows. Further highlights: Shorter design compared to normal disc harrows, enormous area coverage, mobile at up to 19 km/h and extended coupling points - thus suitable for almost all barrel manufacturers and self-propelled machines.




TECHNISCHE MAßE / TECHNICAL DATA

DISC MASTER	ARBEITSBREITE / WORKING WIDTH	STRICH. & BALKEN STITCH. & BARDIS.	SCHEIBEN / DISCS	PS BEDARF / HP REQUIRED	GEWICHT / WEIGHT
LM 4501	4,5 m	22,5 / 72 cm	36	≈ 150 PS/HP	≈ 2.600 kg
LM 5001	5,0 m	22,5 / 72 cm	40	≈ 200 PS/HP	≈ 3.000 kg
LM 6001	6,0 m	22,5 / 72 cm	48	≈ 220 PS/HP	≈ 3.200 kg
LM 7501	7,5 m	22,5 / 72 cm	54	≈ 250 PS/HP	≈ 3.600 kg

SLURRY CULTIVATOR

Güllegrubber / Slurry cultivator



EINSATZZWECK

Unser Güllegrubber öffnet die Bodenstruktur optimal und arbeitet die Gülle effizient ein. Der Boden wird so perfekt mit Nährstoffen angereichert. Mit und ohne Walzen einsetzbar, kurze und kompakte Bauweise und güllerresistent. Der große Abstand von 900 mm zwischen den beiden Zinkenreihen und die speziellen dreiteiligen Vibrozinken mit weitem Federbereich verhindern Verstopfungen. Weitere Highlights: drehbare Schare, senkrechter Verteiler mit 50er Rohrstützen, extra große, gefederte und stufenlos einstellbare Rohrstabwalze. Leuchtenträger mit Warntafeln gehören zur Serienausstattung.

PURPOSE

Our liquid manure cultivator optimally opens up the soil structure and efficiently incorporates the liquid manure. The soil is thus perfectly enriched with nutrients. Can be used with and without rollers, short and compact design and resistant to liquid manure. The large distance of 900 mm between the two rows of tines and the special three-part vibro tines with a wide spring range prevent blockages. Other highlights: rotatable shares, vertical distributor with 50 mm pipe socket, extra large, spring-loaded and continuously adjustable tubular bar roller. Lamp holders with warning signs are part of the standard equipment.



TECHNISCHE MAßE / TECHNICAL DATA

SLURRY CULTIVATOR	ARBEITSBREITE / WORKING WIDTH	ZINKEN / STRICH. TINES / STITCH.	BALKENABSTAND / BARDISTANCE	PS BEDARF / HP REQUIRED	GEWICHT / WEIGHT
6001	6,0 m	24 / 34 cm	92 cm	≈ 150 PS/HP	≈ 2.560 kg
7501	7,5 m	30 / 34 cm	92 cm	≈ 200 PS/HP	≈ 2.930 kg